

Gloss Meter DG60 Series



DG60 SE (Basic edition)



DG60 Pro (Professional edition)



DG60 Max(Enhanced edition)

DG60 SE/Pro/Max

Product Features

- Small —— Only 80 grams weight, size as small as name card
- Accurate —— Pass metrological certification
- Fast —— Single measure time less than 1s
- Long —— Continuous measure 10000 times after rechargeable
- Auto Calibration ——no need manual calibration, measure immediately after power on, intelligent
- Calibration base,Anti-pollution, calibration at any time, to ensure long-term accuracy

Application Examples



Building Material



Glass



Hardware



Automobile



Ceramics



Cellphone

Technical Data

Model	DG60 SE	DG60 Pro	DG60 Max
Calibration	Automatic		
Measure Angle	60°		
Parameter	Gloss(GU)		
Illumination Area	5*10mm		
Measure range	0-200GU	0-1200GU	0-2000GU
Stability	1GU	0-100:0.1GU; > 100:1GU	
Repeatability [*]	1	±0.1 / ±0.1%	0.1 / 0.1%
Battery	Rechargeable, 5000 times continuous tests	Rechargeable, 15000 times continuous tests	Rechargeable, 30000 times continuous tests
Display	IPS full color screen, 135*240, 1.14inch		
Interface	USB	USB,Bluetooth	USB,Bluetooth
Working temperature	0-40℃		
Humidity	< 85%, with no condensation		
Accessories	USB cable,Straps, Manual,Calibration base,Cleaning cloth		
Weight	80g	116g	133g
Size	84mm*70mm*17mm		

^{*} Continuously measure the standard deviation for 30 times. When the measured value is less than 100gu, use the absolute value to evaluate; When the measured value is greater than 100gu, it is evaluated by percentage